


G-BH 1 N

Data sheet 2BH1 430

Side channel blower with IE3-motors

IE3


UL [®] **US**



Performance curves

Vacuum operation

Compressor operation



The performance curves are based on air at a temperature of 15 °C and an atmospheric pressure of 1013 mbar with a tolerance of $\pm 10\%$. The total pressure differences are valid for suction and ambient temperature up to 25 °C. For other conditions please get in touch with us.

Every G-BH pump can be used both as vacuum pump and compressor in continuous operation over the total performance curve range. The motors are available as standard in protection category IP 55 and insulation class F. The vacuum pumps / compressors are UL and CSA approved.

Selection and ordering data

Type										
No.	Fre- quency	Rated			Max. differential pressure ²⁾		Sound pres. Level ³⁾	Efficiency class ⁴⁾	Weight approx.	Order No.
		Voltage ¹⁾	Current	Power	Vacuum	Pressure				
		Hz	V	A	kW	mbar				
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1004 and CNA/CSA 22.2 No 68-09 (certificate number E225239)										
1	50	190-210 Δ	4,35 Δ	0,95	-90	90	63	IE3	19	2BH1430-1AK11
	60	190-210 YY / 380-420 Y	4,25 YY / 2,13 Y	1,10	-80	80	64	IE3		
	60	230 Δ	4,25 Δ	1,10	-80	80	64	NP		
2	50	190-210 Δ	5,6 Δ	1,30	-180	180	63	IE3	21	2BH1430-1AK21
	60	190-210 YY / 380-420 Y	6,3 YY / 3,16 Y	1,60	-180	170	64	IE3		
	60	200 YY	6,3 YY	1,60	-180	170	64	NP		
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1004 and CNA/CSA 22.2 No 68-09 (certificate number E225239)										
1	50	220-240 Δ / 380-420 Y	3,8 Δ / 1,90 Y	0,95	-90	90	63	IE3	19	2BH1430-1AK16
	60	220-240 YY / 440-480 Y	3,7 YY / 1,85 Y	1,10	-80	80	64	IE3		
	60	230 YY / 460 Y	3,7 YY / 1,85 Y	1,10	-80	80	64	NP		
2	50	220-240 Δ / 380-420 Y	4,9 Δ / 2,85 Y	1,30	-180	180	63	IE3	21	2BH1430-1AK26
	60	220-240 YY / 440-480 Y	5,5 YY / 2,75 Y	1,60	-180	170	64	IE3		
	60	230 YY / 460 Y	5,5 YY / 2,75 Y	1,60	-180	170	64	NP		
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1004 and CNA/CSA 22.2 No 68-09 (certificate number E225239)										
1	50	500 Δ	1,76 Δ	1,76	-80	80	63	IE3	19	2BH1430-1AQ15
	60	575 Δ	1,68 Δ	1,10	-80	80	64	NP		
2	50	500 Δ	2,28 Δ	1,30	-180	180	63	IE3	21	2BH1430-1AQ25
	60	575 Δ	2,20 Δ	1,60	-180	170	64	NP		
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1004 and CNA/CSA 22.2 No 68-09 (certificate number E225239)										
1	50	380-420 Δ / 660-725 Y	2,20 Δ / 1,10 Y	0,95	-90	90	63	IE3	19	2BH1430-1AQ17
	60	440-480 Δ	2,10 Δ	1,10	-80	80	64	IE3		
	60	460 Δ	2,10 Δ	1,10	-80	80	64	NP		
2	50	380-420 Δ / 660-725 Y	2,85 Δ / 1,65 Y	1,30	-180	180	63	IE3	21	2BH1430-1AQ27
	60	440-480 Δ	2,75 Δ	1,60	-180	170	64	IE3		
	60	460 Δ	2,75 Δ	1,60	-180	170	64	NP		

- 1) In case of frequency converter operation the standard motor insulation system is suitable for converter input voltages up to 500 V.
- 2) Relief valves available for limiting differential pressure.
- 3) Measuring surface sound pressure level acc. to EN ISO 3744, measured with an equivalent unit at a distance of 1 m. The pump is throttled to an average suction pressure, with piping connected, but no relief valves fitted, tolerance ±3 dB (A).
- 4) The motors according to NEMA MG1-12. NP=NEMA Premium; NEMA Premium includes IE3.









All G-BH match the 2006/42/EC (machinery) and 2006/95/EC (low voltage) directives and the EN 60034 norm "Rotating electrical machines".

Service factor (SF) and motor efficiency according NEMA MG1-12.

Voltage tolerances for three phase motors are +/-10%.

The frequency tolerance is +/- 2 % maximum.

Motor for alternate voltages

Voltage range		Efficiency ⁴⁾	c  US	60 Hz	
50 Hz	60Hz			2BH1...-1.	<input type="checkbox"/>
3~					
200 VΔ	200 V YY / 230 VΔ / 400 VY		•	K	1
190-210 VΔ	190-210 VYY / 220-240 VΔ / 380-420VY		•	K	6
200 VΔ / 230 VΔ / 400 VY	230 V YY / 460 VY		•	K	6
190-210 VYY / 220-240 VΔ / 380-420VY	220-240 VYY / 440-480VY		•	K	6
475-525 V Y	550-600 V Y		•	Q	3
475-525 VΔ	550-600 VΔ		•	Q	5
400 VΔ / 690 V Y	460 VΔ		•	Q	7

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given does not constitute an obligation from our side to deliver as shown.

Elmo Rietschle is a brand of Gardner Denver

**Gardner
Denver**

Your Ultimate Source for Vacuum and Pressure

Gardner Denver Deutschland GmbH

Industriestraße 26
97616 Bad Neustadt - Germany

Tel.: +49 9771 6888-0

Fax: +49 9771 6888-4000

www.gd-elmorietschle.com • er.de@gardnerdenver.com

Gardner Denver Schopfheim GmbH

Roggenbachstraße 58
79650 Schopfheim - Germany

Tel.: +49 7622 392-0

Fax: +49 7622 392-300