

Performance

Tipping load (ISO 14397-1)	2455 kg
Rated operating capacity (ISO 14397-1)	1227 kg
Pump capacity	87.10 L/min
Pump capacity (with high flow option)	115.50 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	18.4 km/h
Max. travel speed (low range)	9.9 km/h

Engine

Make / Model	2.4L BOBCAT ENGINE
Compliance	Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM	55.3 kW
Torque at 1800 RPM (SAE J1995 Gross)	283.9 Nm
Number of cylinders	4
Displacement	2392 cm ³
Fuel tank	90.50 L

Weights

Operating weight	3778 kg
Shipping weight	3378 kg

Controls

Vehicle steering	Hand Levers or optional Selectable Joystick Controls (SJC)
Loader hydraulics tilt and lift	Foot Pedals or optional Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Proportional switch on Hand Levers or optional Selectable Joystick Controls (SJC)

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

Standard Features

Bobcat Interlock Control System (BICS)	Cushioned lift and tilt cylinders
Parking brake	Lift arm support
Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light and electrical power port ¹	Engine/hydraulics system shutdown
Noise reduction kit	Spark Arrester
Operating lights, front and rear	Automatically activated glow plugs
Deluxe instrument panel	Electrically activated proportional front auxiliary hydraulics
Keyless start with password capability	Auxiliary hydraulics: variable flow/maximum flow
Suspension seat	Machine IQ (telematic)
Seat belt	Manual
Seat bar	CE certification
12 x 16.5, Versatile duty tyres	Warranty: 24 months or 2000 hours (whichever occurs first)
Bob-Tach™ frame	


1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

12 x 16.5, 12-ply, Heavy duty tyres, offset rims	Power Bob-Tach™
12 x 16.5, 12-ply, Severe duty tyres	Back-up alarm
Deluxe pressurized cab with heating	Radio
Deluxe pressurized cab with HVAC	Beacon
Selectable Joystick Controls (SJC - R/C Ready)	Work Lights LED
Cloth Suspension Seat	Road Option
High-flow auxiliary hydraulics	Automatic Ride Control
Hydraulic bucket positioning (including ON/OFF switch)	Automatic Reversing Fan
7-pin attachment control	Custom paint color (min order of 5 units)
2 Speed	

Environmental

Operator LpA(98/37 & 474-1)	83 dB(A)
Noise level LWA(EU Directive 2000/14/EC)	101 dB(A)
Whole body vibration (ISO 2631-1)	1.34 ms ⁻²
Whole body vibration uncertainty	0.54 ms ⁻²
Hand-arm vibration (ISO 5349-1)	1.54 ms ⁻²

Dimensions


(A)	4026.0 mm	(J)	3149.0 mm
(B)	2065.0 mm	(K)	851.0 mm
(C)	25.2°	(L)	37.6°
(D)	207.0 mm	(M)	96.6°
(E)	1150.0 mm	(N)	1880.0 mm
(F)	2753.0 mm	(O)	2106.0 mm
(G)	3474.0 mm	(P)	1507.0 mm
(H)	29.4°	(Q)	1832.0 mm
(I)	2489.0 mm		

Attachments

Auger Accessories	Planer Accessories
Augers	Planers
Backhoes	Rear Stabilizers
Bale Forks	Remote Control
Box Blades	Root Grapples
Breaker Accessories	Scarifiers
Breakers	Scrapers
Brushcat™ Rotary Cutters	Seeders
Brush Saws	Skeleton Buckets
Combination Buckets	Snow Blades
Concrete Mixers	Snow Pushers
Construction / Industrial	Snow V-Blades
Buckets	Sod Layers
Diggers	Soil Conditioners
Dozer Blades	Spreader
Drop Hammers	Spreaders
Dumping Hoppers	Steel Tracks
Flail Cutters	Stump Grinders
Graders	Sweepers
Grapples, Industrial	Tillers
Landplanes	Tilt-Tatch
Landscape Rakes	Tree Transplanters
Laser Equipment	Trench Compactors
Low Profile Buckets	Utility Forks
Miscellaneous	Utility Frames
Mixing Buckets	Vibratory Rollers
Mowers	Wood Chippers
Pallet Fork Accessories	
Pallet Forks, Hydraulic	