

**Performance**

Tipping load (ISO 14397-1)	4050 kg
Rated operating capacity (ISO 14397-1)	1426 kg
Pump capacity	88.10 L/min
Pump capacity (with high flow option)	114.70 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range – optional)	14.8 km/h

**Engine**

Make / Model	Bobcat 2.4L, 97/68 EC Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM	55.2 kW
Torque at 1800 RPM (SAE J1995 Gross):	283.9 Nm
Number of cylinders	4
Displacement	2400 cm <sup>3</sup>
Fuel tank	120.00 L

**Weights**

Operating weight	5051 kg
Shipping weight	4394 kg
Ground pressure	43.00 kPa

**Controls**

Vehicle steering	Direction and speed controlled by Selectable Joystick Controls (SJC)
Loader hydraulics tilt and lift	Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Proportional switch on Selectable Joystick Controls (SJC)

**Drive System**

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

**Standard Features**


Selectable Joystick Controls (SJC)	Horn
Deluxe pressurized cab with HVAC	LED Working Lights front and rear
Adjustable suspension seat	Parking brake
3 Point Seat belt	Bob-Tach™ Attachment System
Seat bar	Bobcat Interlock Control System (BICS)
Two Speed Travel	Engine/hydraulics system shutdown
Auxiliary hydraulics: variable flow/maximum flow	Manual
High flow hydraulics	Lift arm support
Dual Direction Bucket Positioning (including ON/OFF switch)	Spark arrestor muffler
5" Deluxe Instrumentation (Radio Ready)	450mm Wide Rubber Tracks
Key start	Machine IQ (telematic)
Backup Alarm	Warranty: 24 months or 2000 hours, whichever occurs first

**Options**

Clear View Cab	Reversible Fan
Auto HVAC	Power Bob-Tach™
7" Touch Display (Integrated Bluetooth, Hands Free Calling, Radio, Reversing Camera)	450mm Wide – Multi Bar Lug Tracks
Torsion Suspension – 5 Link System	Heated Cloth Air ride seat with 3 point seat belt
Radio	Beacon
Reversing Camera	Stroke
Auto Ride Control	

**Environmental**

Operator LpA (98/37 & 474-1)	78 dB(A)
Noise level LWA (EU Directive 2000/14/EC)	103 dB(A)
Whole body vibration (ISO 2631-1)	0.71 ms <sup>-2</sup>
Whole body vibration (ISO 2631-1) uncertainty	0.36 ms <sup>-2</sup>
Hand-arm vibration (ISO 5349-1)	1.84 ms <sup>-2</sup>

**Dimensions**


(A)	4251.8 mm	(J)	3258.5 mm
(B)	2078.7 mm	(K)	1014.0 mm
(C)	27.0°	(L)	37.0°
(D)	234.5 mm	(M)	94.0°
(E)	1504.9 mm	(N)	2032.0 mm
(F)	2893.8 mm	(O)	2300.5 mm
(G)	3736.6 mm	(P)	1531.1 mm
(H)	30.0°	(Q)	1981.1 mm
(I)	2526.1 mm		

**Attachments**

Auger Accessories	Rear Stabilizers
Augers	Remote Control
Box Blades	Root Grapples
Breaker Accessories	Rotary Grinders
Breakers	Sand Cleaners
Brushcat™ Rotary Cutters	Scarifiers
Brush Saws	Scrapers
Combination Buckets	Seeders
Concrete Mixers	Skeleton Buckets
Concrete Pumps	Snow Blades
Construction / Industrial Buckets	Snow Pushers
Dozer Blades	Snow V-Blades
Drop Hammers	Sod Layers
Dumping Hoppers	Soil Conditioners
Flail Cutters	Spreader
Forestry Cutters	Spreaders
Graders	Stump Grinders
Grapples, Industrial	Sweepers
Landscape Rakes	Tillers
Laser Equipment	Tree Transplanters
Low Profile Buckets	Trench Compactors
Miscellaneous	Trenchers
Mixing Buckets	Utility Forks
Pallet Fork Accessories	Utility Frames
Pallet Forks, Hydraulic	Vibratory Rollers
Planer Accessories	Wheel Saws
Planers	Wood Chippers